



Tour Guide System - for museums, factories, powerplants, zoos, theme parks, tourist attractions – just about anywhere where you need to communicate with tour groups.

**1 TRANSMITTER, 11 RECEIVERS,
BATTERIES, 12 SLOT CHARGER**
£1,249.00 + VAT



WT-200

PERSONAL RF TOUR GUIDE SYSTEM

part of the ((soundfields)) range

features

- **More Channels** : 40 Ch./ 863 ~ 865 MHz
- **LCD Screen** : showing operated channels
- Easy to Operate
- Compact & Lightweight
- More Affordable
- 5 year warranty
- Fully compatible for use with the IR-568/89/87 Infrared systems



overall system specification

Oscillation type	PLL synthesized
Carrier frequency range	863~865 MHz
Preprogrammed channels	40 channel selectable
Frequency response	400~4 kHz
Dynamic range	> 70 dB
Operating temperature	-10~50 °C
THD	< 3%
Battery	1.2V AA NiMH rechargeable batteries (1300mAh) x 2 pieces 1.5V AA Alkaline x 2 pieces
Transmission / Reception range	2~50 metres (open field)

system includes

- Transmitter
- 11 Receivers
- Batteries
- 12 slot charger
- 5 year warranty

options

- Personal neck induction loop
- Additional RF receiver
- Additional RF transmitter
- Multiple unit charger

receiver specification

Receiving mode	PLL single-channel receiving
Sensitivity	4 µV @ 20dB SINAD
Audio level	1100 mV @ 2.4 V
RF spurious rejection	60 dB
Adjacent channel performance	60 dB @100kHz50µS
Double intermediate	21.4 MHz / 455 kHz
Antenna	Built-in antenna
Earphone connector	3.5 mm jack socket, for mono or stereo
Battery life Alkaline disposable	> 21 hours typical (3AA*2)
Battery life Ni-HM Rechargeable	19 hours typical (1300 mAh)
Dimensions (D×W×H)	23.1 × 66.2 × 94.5 mm
Weight	126g (batteries included)

transmitter specification

Oscillation type	PLL synthesized controlled Oscillator
RF Power	10 mW (according to regulations)
Spurious Emission	< 250 nW
Microphone	In-built Electrical condenser
Channel Spacing	50 kHz 21.4 MHz / 455 kHz
Audio frequency response	300 Hz to 5 kHz
Maximum modulation	+/- 8 kHz within level limiting
THD	< 2.5 %typical at rated deviation/1 kHz
Operating range	50 ~ 70 Meter (on open field)
Operating temperature	-10 degree to + 55 degree
Antenna	Flexible antenna
Audio input	Mic input and built-in mic
Battery life Alkaline disposable	> 15 hours typical (3AA*2)
Battery life Ni-HM Rechargeable	14 hours typical (1300 mAh)
Dimensions (D×W×H)	23.1 × 66.2 × 94.5 mm
Weight	123g (batteries included)

Specifications subject to change without notice. E&OE



The Old Mending Room, Queens Square Business Park, Huddersfield Road, Honley, Holmfirth, HD9 6QZ

Tel: +44 (0) 1484 667375 Fax: +44 (0) 1484 664310
info@soundfields.co.uk www.soundfields.co.uk

